

## Table of contents

- Import database.sql back in your server with phpmyadmin
  - 1.1.1. Through web interface (Phpmyadmin)
  - 1.1.2. Through command at a terminal screen (command mysql)
  - 1.1.3. Using MySQLDumper or HeidiSql
- 1.2. Working solution of simple interface for the assignment
  - 1.2.1. Wiki Page: r\_test\_xavi
  - 1.2.2. Wiki Page: r\_tests\_xavi\_template
  - 1.2.3. Tracker definition: Tracker Id 5
  - 1.2.4. Tracker fields from Tracker Id 5
- 1.3. Improve interface with tabs for insert, edit, and list runs with your template.
- 1.4. Where to find help from now onwards

## Import database.sql back in your server with phpmyadmin

There are two easy ways to proceed:

1. Through web interface (**Phpmyadmin**), o
2. Through command at a terminal screen (command mysql)

### 1.1.1. Through web interface (Phpmyadmin)

Go to your Phpmyadmin installation.



Select your database name, from the drop down list on the left column in the previous screen.



You have to go to the phpmyadmin tab which says "**SQL**", (versions 2.6.x of Phpmyadmin, like the one in the <https://tiki.org/TikiLiveCD>, or tab "**Import**", included in version 2.8.x of Phpmyadmin, for instance).

Servidor: localhost

bases de dades SQL Estat Variables Jocs de caracters Motors Processos

Exportar Importar

## Importar

Arxiu a importar

Ubicació del fitxer de text  Navega... (Tamany Màxim: 2.048KB)

Joc de caràcters de l'arxiu: utf8

La compressió de l'arxiu importat es detectarà automàticament des de: Res, gzip, bzip2, zip

Importació parcial

Permetre l'interrupció de l'importació en cas de que l'arxiu d'ordres detecti que s'acosta el límit del temps. Pot ser una bona solució per importar arxius grans, però pot trencar transaccions.

Nombre de registres(consultes) a saltar des de l'inici

Format de l'arxiu importat

SQL

Opcions SQL

Aquest format no té opcions

Executar

[Obrir nova finestra de phpMyAdmin](#)

Export tab, in Phpmysql version 2.8.x

### 1.1.2. Through command at a terminal screen (command mysql)



Write a command like

```
mysql -uuser -ppass tiki19 < tiki19_backup_yymmdd.sql
```

In your case, change in the example above:

- *user* for your username at the mysql server
- *pass* for the password for that username at the mysql server
- *tiki19* for your database name, and
- *yymmdd* for the two digits of year, month and day, respectively, for instance, to have your backups easily sorted by name and date of creation also.

If you had exported your database without the option to delete the tables (**Drop tables**, from the Backup instructions through Phpmyadmin) before attempting to restore them from the database backup, then you will have to empty the database tables first. (through phpmyadmin, for instance).

And in case that you have troubles with the character set used to import the database to mysql, you can specify the character set in which your sql database backup is encoded. In order to do so, you can add the parameter **--default-character-set=code** (and as code, you can set for instance utf8 or iso-8859-1)

As an example, in order to set the character set to utf8, you would have to write something like:

```
mysql -uuser -ppass --default-character-set=utf8 tiki19 < tiki19_backup_yymmdd.sql
```

### 1.1.3. Using MySqlDumper or HeidiSql

Both tools can import a sql file. See there homepages for details and examples.

- <http://www.mysqldumper.net/>
- <http://www.heidisql.com/>
- **BigDump** (Staggered import of large and very large MySQL Dumps even through the web-servers with hard runtime limit and those in safe mode)
- **Adminer** (formerly phpMinAdmin) is a full-featured MySQL management tool written in PHP. Conversely to phpMyAdmin, it consist of a single file ready to deploy to the target server.

## 1.2. Working solution of simple interface for the assignment

Two pages are created for the simplest interface.

### 1.2.1. Wiki Page: r\_test\_xavi

```
Hola, mi primera prueba de interfaz web {maketoc} !!# Formulario de entrada de datos {tracker trackerId="5" fields="57:9:25:32:39"} !!# Listado de análisis efectuados {trackerlist trackerId="5" fields="57:9:25:32:39" showlinks="y" ignoreRequestItemId="y" url="tiki-index.php?page=Day 3&itemId="} !!# Resultado del cálculo de la potencia {trackerlist trackerId="5" fields="57:9:25:32:39" tplwiki="r_test_xavi_template" max="1" view="user" showpagination="n"}
```

### 1.2.2. Wiki Page: r\_tests\_xavi\_template

```
{wikiplugin _name=rr} #require(pwr, lib="/home/tuusuario/R/x86_64-pc-linux-gnu-library/2.15" ) require(pwr) pwr.t.test(n={$_9},d={$_25},sig.level={$_32},alternative="{$_39}") {wikiplugin}
```

### 1.2.3. Tracker definition: Tracker Id 5

To learn how to use the code shown below, see <https://doc.tiki.org/Import+Trackers>

```
[TRACKER] autoAssignCreatorGroup = n autoAssignCreatorGroupDefault = n autoAssignGroupItem = n autoCopyGroup = n autoCreateCategories = n autoCreateGroup = n defaultOrderDir = asc defaultOrderKey = -1 defaultStatus = o doNotShowEmptyField = n newItemStatus = o oneUserItem = n orderAttachments = created,hits,filesize ratingOptions = -2,-1,0,1,2 showAttachments = n showComments = n showCreated = n showCreatedBy = n showCreatedView = n showLastComment = n showLastModif = n showLastModifBy = n showLastModifView = n showRatings = n showStatus = n showStatusAdminOnly = n simpleEmail = n useAttachments = n useComments = n useRatings = n userCanTakeOwnership = n writerCanModify = n writerGroupCanModify = n trackerId = 5 name = Tracker de Xavi descriptionIsParsed = n created = 1337277268 lastModif = 1378807353 items = 4
```

### 1.2.4. Tracker fields from Tracker Id 5

To learn how to use the code shown below, see <https://doc.tiki.org/Import+Trackers>

```
[FIELD57] fieldId = 57 name = Nombre del análisis permName = nombreDelAnLisis position = 0 type = t options = isMain = y isTblVisible = y isSearchable = y isPublic = y isHidden = n isMandatory = y description = descriptionIsParsed = n [FIELD70] fieldId = 70 name = Añadido por permName = aAdidoPor position = 10 type = u options = 1,0 isMain = n isTblVisible = y isSearchable = y isPublic = y isHidden = n isMandatory = n description = descriptionIsParsed = n [FIELD9] fieldId = 9 name = n permName = n position = 20 type = n options = 1,0,,,0 isMain = n isTblVisible = n isSearchable = y isPublic = y isHidden = n isMandatory = n description = Tamaño poblacional. Número entero. descriptionIsParsed = n [FIELD25] fieldId = 25 name = d permName = d position = 30 type = n options = 1,0,,,0 isMain = n isTblVisible = n isSearchable = y isPublic = y isHidden = n isMandatory = n description = Tamaño del efecto. Número decimal, normalmente entre 0 y 1,0. Ten en cuenta que el carácter a usar como separador decimal depende del navegador que uses: es la coma (,) con Chrome y Safari, y el punto (.) con Firefox, Opera, IE9 y afines. descriptionIsParsed = n [FIELD32] fieldId = 32 name = sig.level permName = sigLevel position = 40 type = n options = 1,0,,,0 isMain = n isTblVisible = n isSearchable = y isPublic = y isHidden = n isMandatory = n description = Nivel de significación. Número decimal, entre 0 y 1,0. Ten en cuenta que el carácter a usar como separador decimal depende del navegador que uses: es la coma (,) con Chrome y Safari, y el punto (.) con Firefox, Opera, IE9 y afines. descriptionIsParsed = n [FIELD39] fieldId = 39 name = alternative permName = alternative position = 50 type = d options = greater,less,less,two.sided isMain = n isTblVisible = n isSearchable = y isPublic = y isHidden = n isMandatory = n description = descriptionIsParsed = n
```

## 1.3. Improve interface with tabs for insert, edit, and list runs with your template.

Similarly to the interface you can find in the `r_test3` page, created by the profile `r_test`, using [PluginTABS](#) and [PluginFADE](#), for instance.

## 1.4. Where to find help from now onwards

Tiki Forums (in general):

- English: <https://tiki.org/forums>
- Spanish: <https://tiki.org/forum15>
- Catalan: <https://tiki.org/forum16>

Forum about Tiki & PluginR

- Spanish: <http://r-es.org/forum3>
- English: <https://tiki.org/forum24>

Email lists:

- Tiki Users:  
<https://lists.sourceforge.net/mailman/listinfo/tikiwiki-users>
- Tiki Developers  
<https://lists.sourceforge.net/mailman/listinfo/tikiwiki-devel>

IRC Canal (chat):

- <http://tiki.org/Irc>